

 CRISTALENS

ARTIS[®] PL E

HYDROPHOBIC LENS



PRELOADED

► **Monofocal**



MADE IN **FRANCE**

CE 0459

TECHNICAL SPECIFICATIONS

Lens type	For implantation in the capsular bag
Optic diameter	6.15 mm (from 0.0D to +9.5D) 6.00 mm (from +10.0D to +25.0D) 5.80 mm (from +25.5D to +35.0D)
Overall diameter	11.00 mm (from 0.0D to +9.5D) 10.79 mm (from +10.0D to +25.0D) 10.50 mm (from +25.5D to +35.0D)
Design	One-piece square edge on 360°
Optic design	Monofocal Aspherical with negative spherical aberration to partly correct corneal spherical aberration
Angulation	5°
Material	Hydrophobic CBK 1.8 from Cristalens
Dioptric powers	From 0.0D to +35.0D by 0.5D
Estimated A-Constant (SRK-T)	119.3 Ultrasound biometry 119.7 Interference laser biometry
Suggested anterior chamber depth (ACD)	5.77 mm Ultrasound biometry 6.03 mm Interference laser biometry
Refractive index	1.54
Sterilization	Ethylene oxide
Injection system	Preloaded system
Recommended incision size	2.0 mm



www.cristalens-international.com

 **CRISTALENS INDUSTRIE**

4 rue Louis de Broglie - 22300 Lannion - FRANCE
Tel +33 (0)2 96 48 92 92 - Fax +33 (0)2 96 48 97 87

