



1) Rapid Warm-up & Dry System




2) Convenient and Safe Sterilizing Agent



3) 7" full touch LCD, Easy Monitoring the Cycle Information



4) Plug and Play



5) Spacious chamber size



6) Auto Interlock & Open System



7) Double door system



Sterilizing Agent		Hydrogen Peroxide 20 Cycles/Bottle
Total Cycle Time	Quick	30+5min
	Standard	40+5min
	Special	50+5min
Cycle Temperature		50±5°C
SAL(Sterility Assurance Level)		10 ⁻⁶
By-products		Oxygen and vapor water only
Lumenclaims		Rigid lumen & Flexible lumen, Endoscopes
Chamber	Type Material	Rectangular Stainless Steel(SUS)
Dimensions	Overall Chamber	120M : 680mm(W) X 1575(H) X 940(D) / 120D : 680mm(W) X 1575(H) 785(D) 120M : 420mm(W) X 400(H) X 775(D) / 120D : 420mm(W) X 450(H) 720(D)
Volume		Total : 130 Liters
Weight		290Kg
Control		Microprocessor & Windows CE embedded
Cycle Information		Screen, Printer, USB, 100/10Mbps Ethernet(Optional)
PM Cycle		Automatic Alarm & Setup
Electrical		110V / 220V, 50 / 60Hz, 1Phase, 3000W
Installation Requirements		Double Door : Front, Rear(100cm), Left, Right(10cm) Single Door : Front(100cm), Rear, Left, Right(10cm) Placement : Built-in wheels provide mobility
Room Conditions		5~40°C, 0~95%RH(Non-Condensing)
Printer		Built-in Thermal Printer(60Ø Roll Paper) Cycle Parameters(Temp, Pressure, Time, Daily&Total Cycle, etc) Alarm & Error Display
Others		Emergency Stop(Front), Operator ID Login, Self-Diagnosis, Multi-Language, RFID Coding System