



1) Rapid Warm-up & Dry System




2) Convenient and Safe Sterilizing Agent



3) 7" full touch LCD, Easy Monitoring the Cycle Information




4) Plug and Play



5) All-in-one Basket Tray



6) Automatic PM Alarm System



Sterilizing Agent		Hydrogen Peroxide 40 Cycles/Bottle
Total Cycle Time	Quick	25+5min
	Standard	35+5min
	Special	45+5min
Cycle Temperature		50 ± 5°C
SAL [Sterility Assurance Level]		10 ⁻⁶
By-products		Oxygen and vapor water only
Lumenclaims		Rigid lumen & Flexible lumen, Endoscopes
Chamber	Type Material	Rectangular Stainless Steel (SUS)
Dimensions	Overall	530mm(W) X 740(H) X 790(D)
	Chamber	300mm(W) X 220(H) X 640(D)
Volume		Total : 40 Liters
Weight		120Kg
Control		Microprocessor & Windows CE embedded
Cycle Information		Screen, Printer, USB, 100/10Mbps Ethernet (Option)
PM Cycle		Automatic Alarm & Setup
Electrical		110V / 220V, 50 / 60Hz, 1Phase, 1600W
Installation Requirements		Front : 100cm Rear, Left side, Right side : 10cm Placement : Built-in wheels provide mobility
Room Conditions		5~40°C, 0~95%RH (Non-Condensing)
Printer		Built-in Thermal Printer (60Ø Roll Paper) Cycle Parameters (Temp, Pressure, Time, Daily & Total Cycle, etc) Alarm & Error Display
Others		Emergency Stop (Front), Operator ID Login, Self-Diagnosis, Multi-Language, RFID Coding System
Cart (Option)		530mm(W) X 720(H) X 710(L) / 50kg