




**7) Built-in Thermal Printer, Printout with Actual Cycle Information**




**8) Login Function**



**9) Table-top Model**



**10) Auto Interlock & Open System**



**11) Useful Cart**



**12) USB History Memory- and Monitoring System**



Sterilizing Agent		Hydrogen Peroxide 40 Cycles/Bottle
Total Cycle Time	Quick	25+5min
	Standard	35+5min
	Special	45+5min
Cycle Temperature		50± 5°C
SAL(Sterility Assurance Level)		10 <sup>-6</sup>
By-products		Oxygen and vapor water only
Lumenclaims		Rigid lumen & Flexible lumen, Endoscopes
Chamber	Type	Rectangular
	Material	Stainless Steel (SUS)
Dimensions	Overall	530mm(W) X 780(H) X 855(D)
	Chamber	320mm(W) X 230(H) X 700(D)
Volume		Total : 50 Liters
Weight		140Kg
Control		Microprocessor & Windows CE embedded
Cycle Information		Screen, Printer, USB, 100/10Mbps Ethernet(Optional)
PM Cycle		Automatic Alarm & Setup
Electrical		110V / 220V, 50 / 60Hz, 1Phase, 1800W
Installation Requirements		Front : 100cm Rear, Left side : 10cm Placement : Built-in wheels provide mobility
Room Conditions		5~40°C, 0~95%RH(Non-Condensing)
Printer		Built-in Thermal Printer(60Ø Roll Paper) Cycle Parameters(Temp, Pressure, Time, Daily&Total Cycle, etc) Alarm & Error Display
Others		Emergency Stop(Front), Operator ID Login, Self-Diagnosis, Multi-Language, RFID Coding System
Cart(Optional)		530mm(W) X 720(H) X 760(L) / 50kg